### § 22.515

- (2) Parties seeking authority to disaggregate must submit with their partial assignment application a certification signed by both parties stating which of the above requirements they meet.
- (3) Disaggregatees must submit supporting documents showing compliance with their coverage requirements as set forth in §22.503 (k)(1), (2) and (3).
- (4) Parties that accept responsibility for meeting the coverage requirements and later fail to do so will be subject to automatic license cancellation without further Commission action.

[64 FR 33784, June 24, 1999]

# § 22.515 Permissible communications paths.

Mobile stations may communicate only with and through base stations. Base stations may communicate only with mobile stations and receivers on land or surface vessels.

### §22.527 Signal boosters.

Licensees may install and operate signal boosters on channels listed in §22.531 only in accordance with the provisions of §22.165 governing additional transmitters for existing systems. Licensees must not allow any signal booster that they operate to cause interference to the service or operation of any other authorized stations or systems.

[61 FR 31051, June 19, 1996]

#### § 22.529 Application requirements for the Paging and Radiotelephone Service.

In addition to information required by subparts B and D of this part, applications for authorization in the Paging and Radiotelephone Service contain required information as described in the instructions to the form. Site coordinates must be referenced to NAD83 and be correct to +-1 second.

- (a) Administrative information. The following information, associated with Form 601, is required as indicated. Each application of any type, including applications for paging geographic area authorizations, must contain one and only one Schedule A.
- (1) The purpose of the filing is required for each application of any type.

- (2) The geographic area designator, channel and geographic area name are required only for each application for a paging geographic area authorization.
- (3) The FCC control point number, if any, the location (street address, city or town, state), the telephone number and an indication of the desired database action are required only for each application proposing to add or delete a control point.
- (4) The FCC location number, file number and location (street address, city or town, state) of authorized facilities that have not been constructed are required only for each application requesting an extension of time to construct those facilities.
- (b) Technical data. The following data, associated with FCC Form 601, are required as indicated for each application. Applications for a paging geographic area authorization must not contain Schedule B. Other type of applications may contain as many Schedule Bs as are necessary for the intended purpose.
- (1) For each transmitting antenna site to be added, deleted or modified, the following are required: an indication of the desired database action, the Commission location number, if any, the street address or other description of the transmitting antenna site, the city, county and state, the geographic coordinates (latitude and longitude), correct to ±1 second, of the transmitting antenna site (NAD83), and in the case of a proposed relocation of a transmitting antenna, the Commission location number and geographic coordinates, correct to ±1 second, of the transmitting antenna site (NAD83) to which the geographic coordinates of the current location are referenced.
- (2) For each transmitting antenna site to be added, deleted or modified, the following supplementary information is required: An indication as to whether or not the transmitting antenna site is within 200 kilometers (124 miles) of the U.S.-Mexico border, and an indication as to whether or not the transmitting antenna site is North of Line A or East of Line C. Line A and Line C are defined in §2.1 of this chapter. For each adjacent geographic area within 200 kilometers (124 miles) of each transmitting antenna site to be

added, deleted or modified, the geographic area designator and name, and the shortest distance (in kilometers) to the boundary of that geographic area.

- (3) The height (in meters) above average terrain of the center of radiation of the antenna, the beamwidth of the main lobe of the horizontal radiation pattern of the electric field of the antenna, the height (in meters) to the tip of the antenna above ground level, a polar plot of the horizontal gain pattern of the antenna, the antenna gain in the maximum lobe and the electric field polarization of the wave emitted by the antenna when installed as proposed.
- (i) The center frequency of the requested channel, the transmitter classification (e.g. base, fixed mobile), the designator for any non-standard emission type to be used, including bandwidth and modulation type, and the maximum effective radiated power.
- (ii) For each of the eight cardinal radials, the antenna height above the average elevation along the radial, and the effective radiated power of each transmitter in the direction of the radial.
- (iii) For each transmitter proposed to transmit on a channel reserved for point-to-multipoint operation involving transmission to four or more points of communications (i.e. base transmitters), the following is required for each point of communication: an indication of the desired database action, the location (city or town, state), and the geographical coordinates (latitude and longitude, NAD 83).
- (c) Upon request by an applicant, licensee, or the Commission, a part 22 applicant or licensee of whom the request is made shall furnish the antenna type, model, and the name of the antenna manufacturer to the requesting party within ten (10) days of receiving written notification.

[62 FR 11635, Mar. 12, 1997, as amended at 63 FR 68945, Dec. 14, 1998; 64 FR 53240, Oct. 1, 1999]

## PAGING OPERATION

# § 22.531 Channels for paging operation.

The following channels are allocated for assignment to base transmitters

that provide paging service, either individually or collectively under a paging geographic area authorization. Unless otherwise indicated, all channels have a bandwidth of 20 kHz and are designated by their center frequencies in MegaHertz.

_					
Low VHF Channels					
35.20	35.46	43.20	43.46		
35.22	35.50	43.22	43.50		
35.24	35.54	43.24	43.54		
35.26	35.56	43.26	43.56		
35.30	35.58	43.30	43.58		
35.34	35.60	43.34	43.60		
35.38	35.62	43.38	43.62		
35.42	35.66	43.42	43.66		
High VHF Channels					
152.24	152.84	158.10	158.70		
UHF Channels					
931.0125	931.2625	931.5125	931.7625		
931.0375	931.2875	931.5375	931.7875		
931.0625	931.3125	931.5625	931.8125		
931.0875	931.3375	931.5875	931.8375		
931.1125	931.3625	931.6125	931.8625		
931.1375	931.3875	931.6375	931.8875		
931.1625	931.4125	931.6625	931.9125		
931.1875	931.4375	931.6875	931.9375		
931.2125	931.4625	931.7125	931.9625		
931.2375	931.4875	931.7375	931.9875		

- (a)–(b) [Reserved]
- (c) Upon application using FCC Form 601, common carriers may be authorized to provide one-way paging service using the leased subcarrier facilities of broadcast stations licensed under part 73 of this chapter.
- (d) Occasionally in case law and other formal and informal documents, the low VHF channels have been referred to as "lowband" channels, and the high VHF channels have been referred to as "guardband" channels.
- (e) Pursuant to the U.S.-Canada Interim Coordination Considerations for 929–932 MHz, as amended, only the following UHF channels may be assigned in the continental United States North of Line A or in the State of Alaska East of Line C, within the indicated longitudes:
- (1) From longitude W.73° to longitude W.75° and from longitude W.78° to longitude W.81°:

931.0125	931.1125	931.1875	931.2625
931.0375	931.1375	931.2125	931.8625
931 0625	931 1625	931 2375	

(2) From longitude W.81° to longitude W.85°:

931.0125 931.2125 931.3875 931.5875